



**HERGENHAN**  
Technical Trading

Vollrollige  
Zylinderrollenlager  
-mehreihig

Welle Ø	Bezeichnung	d	D	B	r	s	F	Gewicht kg	Tragzahlen kN		max. Drehzahl min <sup>-1</sup>	
		mm	mm	mm	mm	mm	mm		C <sub>0</sub>	C	Fett	Öl
40	NNU6908V	40	62	40	0,6	1,8	40,85	0,50	175	82	2600	4800
	NNU6008V	40	68	50	1,0	1,8	43,15	0,90	227	113	2400	4500
45	NNU6909V	45	68	40	0,6	1,8	52,35	0,60	191	87	2200	4300
	NNU6009V	45	75	54	1,0	1,3	53,65	1,00	302	155	2200	4300
50	NNU6910V	50	72	40	0,6	1,8	56,15	0,60	205	91	2200	4300
	NNU6010V	50	80	54	1,0	1,3	59,40	1,20	338	162	2000	4000
55	NNU6911V	55	80	45	1,0	1,1	62,20	0,80	284	127	1900	3800
	NNU6011V	55	90	63	1,1	1,4	64,85	1,70	439	210	1800	3600
60	NNU6912V	60	85	45	1,0	1,1	67,00	0,90	310	133	1800	3600
	NNU6012V	60	95	63	1,1	1,4	71,50	2,00	485	222	1600	3200
65	NNU6913V	65	90	45	1,0	1,1	71,75	0,90	333	139	1600	3200
	NNU6013V	65	100	63	1,1	1,4	76,00	1,90	520	229	1500	3000
70	NNU6914V	70	100	54	1,0	1,3	78,45	1,40	445	188	1500	3000
	NNU6014V	70	110	71	1,1	1,4	81,75	2,80	635	285	1400	2800
75	NNU6915V	75	105	54	1,0	1,3	84,20	1,50	475	195	1400	2800
	NNU6015V	75	115	71	1,1	1,4	86,80	3,20	680	300	1300	2600
80	NNU6916V	80	110	54	1,0	1,3	88,00	1,60	490	200	1300	2600
	NNU6016V	80	125	80	1,1	1,5	95,00	4,00	820	360	1200	2400
90	NNU6918V	90	125	63	1,1	1,4	100,50	2,40	670	270	1100	2200
	NNU6018V	90	140	90	1,5	1,8	105,00	5,40	1040	450	1100	2200
100	NNU6920V	100	140	71	1,1	1,4	112,25	3,50	890	350	1000	2000
	NNU6020V	100	150	90	1,5	1,8	115,00	5,80	1150	480	1000	2000
110	NNU6922V	110	150	71	1,1	1,4	122,50	3,80	970	360	950	1900
	NNU6022V	110	170	109	2,0	2,4	126,50	9,30	1600	630	950	1900



**HERGENHAN**  
Technical Trading

Welle Ø	Bezeichnung	d mm	D mm	B mm	r mm	s mm	F mm	Gewicht kg	Tragzahlen kN		max. Drehzahl min <sup>-1</sup>	
									C <sub>o</sub>	C	Fett	Öl
120	NNU6924V	120	165	80	1,1	1,5	132,00	5,30	1200	430	850	1700
	NNU6024V	120	180	109	2,0	2,4	138,00	10,00	1700	660	850	1700
130	NNU6926V	130	180	90	1,5	1,8	143,50	7,20	1500	530	800	1600
	NNU6026V	130	200	125	2,0	2,4	152,00	15,00	2100	850	750	1500
140	NNU6928V	140	190	90	1,5	1,8	156,25	7,50	1600	540	750	1500
	NNU6028V	140	210	125	2,0	2,4	161,00	15,60	2300	870	700	1400
150	NNU6930V	150	210	109	2,0	2,4	168,25	12,00	2100	720	700	1400
	NNU6030V	150	225	136	2,1	2,8	172,50	20,00	2600	1000	650	1300
160	NNU6932V	160	220	109	2,0	2,4	179,75	12,60	2200	750	650	1200
	NNU6032V	160	240	145	2,1	2,9	184,00	24,00	3000	1200	600	1100
170	NNU6934V	170	230	109	2,0	2,4	187,50	13,50	2300	770	600	1100
	NNU6034V	170	260	160	2,1	3,0	195,25	32,00	3600	1350	550	1000
180	NNU6936V	180	250	125	2,0	2,4	201,00	20,00	2900	1000	550	1000
	NNU6036V	180	280	180	2,1	3,5	210,50	43,00	4300	1650	500	900
190	NNU6938V	190	260	125	2,0	2,4	209,75	22,00	3000	1000	550	950
	NNU6038V	190	290	180	2,1	3,5	223,25	45,00	4600	1700	500	900
200	NNU6940V	200	280	145	2,1	2,9	224,50	30,00	3700	1250	500	850
	NNU6040V	200	310	200	2,1	4,0	232,50	57,00	5200	1950	450	800
220	NNU6944V	220	300	145	2,1	2,9	244,75	32,00	4000	1350	450	800
	NNU6044V	220	340	218	3,0	4,3	252,50	75,00	6300	2300	430	750
240	NNU6948V	240	320	145	2,1	2,9	265,25	33,00	4300	1400	400	700
	NNU6048V	240	360	218	3,0	4,4	275,50	80,00	6800	2400	370	650
260	NNU6952V	260	360	180	2,1	3,5	293,25	58,00	6000	1950	360	640
	NNU6052V	260	400	250	4,0	4,6	303,50	120,00	8700	3100	350	600



# HERGENHAN

*Technical Trading*


Welle Ø	Bezeichnung	d mm	D mm	B mm	r mm	s mm	F mm	Gewicht kg	Tragzahlen kN		max. Drehzahl min <sup>-1</sup>	
									C <sub>0</sub>	C	Fett	Öl
280	NNU6956V	280	380	180	2,1	3,5	312,50	61,00	6400	2000	340	600
	NNU6056V	280	420	250	4,0	4,6	321,50	125,00	9200	3200	320	550
300	NNU6960V	300	420	218	3,0	3,8	336,50	96,00	8300	2700	320	560
	NNU6060V	300	460	290	4,0	5,6	347,00	180,00	11300	4000	300	530
320	NNU6964V	320	440	218	3,0	3,8	359,50	100,00	9000	2800	300	520
	NNU6064V	320	480	290	4,0	5,6	367,00	190,00	12500	4100	280	500
340	NNU6968V	340	460	218	3,0	3,8	374,70	108,00	9300	2800	280	500
	NNU6068V	340	520	325	5,0	6,5	391,50	260,00	14500	4900	260	470
360	NNU6972V	360	480	218	3,0	3,8	397,60	112,00	10000	3000	260	480
	NNU6072V	360	540	325	5,0	6,5	413,00	270,00	16000	5200	240	450
380	NNU6976V	380	520	250	4,0	4,9	419,20	163,00	12000	3600	240	450
	NNU6076V	380	560	325	5,0	6,5	436,00	280,00	17500	5600	240	450
400	NNU6980V	400	540	250	4,0	5,0	445,90	170,00	13000	3800	240	450
	NNU6080V	400	600	355	5,0	6,0	459,00	365,00	19000	6200	220	420
420	NNU6984V	420	560	250	4,0	5,0	463,70	175,00	14000	3900	220	430
	NNU6084V	420	620	355	5,0	6,0	485,00	380,00	20000	6400	200	400
440	NNU6988V	440	600	290	4,0	5,6	489,00	245,00	16000	4800	220	420
	NNU6088V	440	650	375	6,0	7,0	509,00	440,00	22000	7000	200	400



**HERGENHAN**  
*Technical Trading*

## Zusätzliche Informationen:

Bauform:



NNU69..V  
NNU60..V